

Installing a Debris Catcher on the Serene, Timra Vista

The debris catcher (*fig. 1*) is optional and can be purchased from Faber. Besides the debris catcher, a 4 inch flexible pipe (*fig 2*) with a length of 500mm has to be purchased, together with a glass fibre seal (*fig.3*). To install the Timra Vista with these parts properly, follow the following instructions.

1. Place the glass fibre seal around the firebox (*fig. 4*);
2. Position the firebox in the fireplace opening. Make sure that the glass fibre seal seals off any holes between the firebox and the fireplace opening.
3. Follow steps 2-5 of paragraph 4.3 of the instruction manual of the Timra Vista;
4. Slide the debris catcher on the 4 inch flexible pipe;
5. Secure the vent connector unit to the flexible pipe with debris catcher. Use the inner collar of the vent connector unit (*see fig.5*).
6. Slide the clamping plate with the lip upward under the vent connector. The flue connector and pipe rests on the clamping plate. Make sure that the lip of the clamping plate goes in the slot on the front of the firebox (*see fig.6*).
7. Slide the burner chamber into the firebox.
8. Pull the clamping plate out. The flue collar plate makes contact with the burner chamber.
9. Turn the clamping plate up side down and slide the plate between the guides so that its ends grip around the pipe opening (*see fig. 7*). Make sure that the flue collar plate is pressed onto the burner chamber;
10. Continue by following steps 11-14 of paragraph 4.3 of the instruction manual of the Timra Vista.

Note: steps 4-7 are the same as steps 7-10 described in paragraph 4.3 of the instruction manual of the Timra Vista.

